



## Arriva Furniture Lift

**TEST THE BEST** 

# The Böcker Arriva Furniture Lift

## The workhorse among the furniture lifts – extra strong and robust

The powerful furniture lifts are able to transport maximum loads of 400 kg. Modern design as well as the superior and legendary Böcker technology are core characteristics of the Arriva series. The enormous stability of the Böcker profiles is of particular importance in this context. No other furniture lift offers comparable strengths. .



## Advantages at a glance

- Available with a maximum payload of 300 or 400 kg (Standard/Maxi)
- Side panels of the platform are foldable at 90° and 180° as well as removable
- Large, plane furniture platform with low, back-friendly loading height
- Efficient due to low-maintenance systems: precise cable guide, maintenance free guide rolls with broad profile, optimal access to the engine, manoeuvring drive with positive connection
- Solid stand thanks to zinc-plated supports
- Maximum reliability and ease of use just like all Böcker Furniture Lifts



## A strong partner for any removal!

The completely plane platform with foldable and removable side panels as well as the extremely low loading height contribute to safe working in order to spare your back. Quick assembly, convenient and safe operation, excellent transport characteristics – the Böcker Arriva Furniture Lift ensures most efficient operations in any situation.

## Further advantages in detail



Integrated rear lights



Operation panel for manoeuvring-drive



Completely plane platform surface

## Technical Data

Model	HD 26 / 1-6 LH	HD 30 / 1-7 LH	HD 30 / 2-8 LH	HD 34 / 1-8 LH	HD 37 / 2-8 LH
Payload [kg] Standard/Maxi	300/400	300/400	300/400	300/400	300/400
Gross vehicle weight [kg]	1,800 <sup>1)</sup>	1,800 <sup>1)</sup>	2,240 <sup>1)</sup>	2,240 <sup>1)</sup>	2,240 <sup>1)</sup>
Max. axle load [kg]	1,800 <sup>1)</sup>	1,800 <sup>1)</sup>	2,240 <sup>1)</sup>	2,240 <sup>1)</sup>	2,240 <sup>1)</sup>
<b>Average carriage speed</b>					
Honda GX 390 [m/min]	45	45	45	45	45
Honda GX 620 silent /turbo [m/min]	45/60	45/60	45/60	45/60	45/60
<b>Dimensions</b>					
Total length [mm]	7,150	7,200	7,200	7,250	8,550
Total width [mm]	1,650 <sup>1)</sup>	1,650 <sup>1)</sup>	1,760 <sup>1)</sup>	1,760 <sup>1)</sup>	1,760 <sup>1)</sup>
<b>Guide rails:</b> Lenght rail package [mm] Track width [mm]	5,360 540	5,415 540	5,415 540	5,470 540	6,810 540
Extendable to [m]	25.76	29.77	29.77	33.10	36.48
Towing bar	Rigid or height-adjustable	Rigid or height-adjustable	Rigid or height-adjustable	Rigid or height-adjustable	Rigid or height-adjustable
Drive unit	Hydraulic unit	Hydraulic unit	Hydraulic unit	Hydraulic unit	Hydraulic unit
Version Standard	Honda GX 390	Honda GX 390	Honda GX 390	Honda GX 390	Honda GX 390
Version Maxi	Honda GX 620	Honda GX 620	Honda GX 620	Honda GX 620	Honda GX 620

<sup>1)</sup> 2,300 kg with manoeuvring drive and tires 215/75 R 16 C (width 1,850 mm)

All rights reserved for changes in dimension and construction

## The strong Furniture Lift for any situation



Infinitely variable, gas spring spindle  
17–87° (optional)



Automatic, hydraulic handle lock  
(optional)



Electric control via cable operation



Solid support wheel  
(optional as double support wheel)



Infinitely variable, hydraulically  
releasable live ring lock

Wheels of the head piece  
laterally adjustable (optional)

Vertically and horizontally adjustable  
guide rails – for an extremely smooth  
rail and carriage operation

Hydraulic live ring adjustment (optional)

Chassis with special finish  
made of torsion proof  
C-profiles for simple and safe  
attachment of accessories.





Hand-held radio transmitter for operation from the top end



Extra powerful engines (e.g. Honda GX 620) with turbo switch



Side panels foldable 90°/180° and completely removable

Noise protection hood (optional)



Zinc-plated crank outriggers with locking pins



Powerful manoeuvring drive with positive connection (optional)



**Albert Böcker GmbH & Co. KG**  
Lippestraße 69 · D-59368 Werne  
Fon +49 (0) 23 89/79 89-0  
Fax +49 (0) 23 89/53 22 04  
Mail [boecker@boecker-group.com](mailto:boecker@boecker-group.com)  
Web [www.boecker-group.com](http://www.boecker-group.com)